




Description	Product Code	Weight (Lbs.)
Bases		
36" x 36" x 36" ID Knockout Base	363636BKO	2,980
36" x 36" x 36" ID Base	363636B	4,310
36" x 36" x 48" ID Knockout Base	363648BKO	3,960
36" x 36" x 48" ID Base	363648B	5,360
Risers		
36" x 36" x 6" ID Riser	36366R	485
36" x 36" x 12" ID Riser	363612R	1,010
36" x 36" x 24" ID Riser	363624R	2,060
36" x 36" x 36" ID Riser	363636R	3,110
Slab Top		
36" x 36" x 6" Slab Top with 30" x 30" Opening	36366ST3030	735
Cast Iron		
30" x 30" Type A Frame	3030FA	210
30" x 30" Type A Narrow Slot Grate	3030GNS	235
30" x 30" Type A Square Hole	3030GSH	265
30" x 30" Type A ADA Grate	3030GADA	225



Exploded Isometric View
Scale: 1/2' = 1'



Concrete
28 day compressive strength of 4,500 PSI
Bottoms to be monolithic at floor and at first stage of wall

Cement
Per ASTM C150: Type I/II

Cast Iron
Meets ASTM A48 and CL35B Standards

Loading
Live Load - H-20

Reinforcement
Rebar per ASTM A615 Grade 60
Wire Mesh per ASTM A1064

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ROCK SOLID PRECAST, LP. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ROCK SOLID PRECAST, LP IS PROHIBITED.

Rock Solid Precast, L.P.

11393 Sleepy Hollow Road
Conroe, TX 77385

PO Box 8066
The Woodlands, TX 77387

(281) 364-7474

TITLE

36" x 36" Type A Submittal

DWG. NO.
36A Drawing Submittal

DRAWN CHECKED WEIGHT
MKK

Varies