



Capacity (Gal.)	L	W	H	IN	OUT	T	T1	Base Weight (Lbs.)	Top Weight (Lbs.)
500	102"	67"	48"	39"	36"	4"	4"	8,129	3,092
750	102"	67"	66"	53"	50"	4"	4"	11,919	3,092
1,000	102"	67"	66"	57"	54"	4"	4"	11,921	3,092
1,250	110"	68"	78"	57"	54"	6"	6"	18,253	3,424
1,500	110"	68"	78"	69"	66"	6"	6"	18,260	3,424

Concrete
28 day compressive strength of 4,500 PSI

Cement
Per ASTM C150: Type I

Cast Iron
Meets ASTM A48 and CL35B Standards

Reinforcement
Rebar per ASTM A615 Grade 60

Rock Solid Precast, L.P.

11393 Sleepy Hollow Road PO Box 8066
Conroe, TX 77385 The Woodlands, TX 77387

(281) 364-7474

TITLE

750 - 1,500 Gallon Grease Trap

DWG. NO. Grease Trap Submittal

DRAWN	CHECKED	WEIGHT
MKK		

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ROCK SOLID PRECAST, LP. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ROCK SOLID PRECAST, LP IS PROHIBITED.